

DIGIMIC lean⁺ modular

6+1 built in microphone unit with Channel selector, Custom Chassis and optional RFID identification

Article no.: 05.1234.32/05.1234.32.CH and 05.1235.32/05.1235.32.CH



Application example

Description

DIGIMIC lean⁺ modular is the delegate unit for your conference. Discreetly integrated into the tabletop, it offers the best conditions for your delegates.

The DIGIMIC lean⁺ modular has a microphone, headphone jack, channel selector, voting function and optional identification. In addition, the lean⁺ modular offers space for individual solutions - such as USB or network connections. The lean⁺ modular unit is operated via five keys - all settings are visible on the display.

The channel selector transmits up to 32 languages - original sound and 31 languages. The DIGIMIC lean⁺ modular unit with RFID card reader is available as an option. You can use the RFID card to register and identify all conference topics.

In addition to the delegate version, the DIGIMIC lean⁺ modular is also available as a chairman version. The chairman version gives special priority to the chairman of a conference. The chairman can mute all delegate units with the override button.

Technical Data

Features

- Discreetly integrated into the table top
- Compact installation
- Microphone button lights up red when speaking
- Adjustable headphone volume
- OR + 31 language channels
- 5 function keys
- Identification using RFID card
- Space for individual solutions (e.g. USB or network connection)
- Chairman Version: override key for the Chairman of a conference

Digital Audio

- High quality audio signal
- Sample rate: 48 kHz
- Frequency response: 20 - 20.000Hz

Connectors

- 3.5mm jack socket
- 2x RJ45 DIGIMIC bus

Housing

- Housing: Aluminum with plastic chassis
- LxW: 363,5 x 73 mm
- Weight: approx. 360 g

System requirements

Required system components:

- DCen32
Article no.: 05.0050
- DCen32 mini
Article no.: 05.0420

Microphones:

- TMD/01
Article no.: 01.0711
- TM58/6
Article no.: 01.0560
- TMD/382
Article no.: 01.0740
- TMD/CL
Article no.: 01.0750

(all microphones are available in different lengths)

Other components:

- DExt
Article No.: 05.0025
- DDol32
Article no.: 05.0750
- RFID card
Article no.: 16.3870

Software:

BrählerOS conference software for network-based control of all DIGIMIC system components. Simple configuration of all delegate units from one central location.

Possible combinations

The lean+ modular in System 6+1 Custom is available in various versions:



All lean+ modular units are optionally available as a chairman unit with an additional override button to mute the delegate microphones.

Article no.: 05.1234.32.CH or 05.1235.32.CH



Delegate unit with microphone, headphone jack and channel selector. The custom Chassis insert for free placement – e.g. USB-Port.

Article no.: 05.1234.32



Optional RFID card reader for registration and identification of delegates

Article no.: 05.1235.32



Application example Power Frame silver-grey



Application example Power Frame Cover Aluminum

Frame and cover are available in different colors

The following inserts are available for the custom chassis:

- DVI-I socket
- Stainless Steel Button
- Stainless Steel Button, blue illuminated
- Keystone: Cover, HDMI, Jack, mini DisplayPort, USB
- HDMI socket
- XLR, Microphone (3-Pin) socket and plug
- Keystone Holder Single and Double, Black
- USB Charger
- DisplayPort socket
- USB 2.0 A / B
- VGA socket+miniature jack cable
- Keystone Ethernet Cat6

Socket modules are available as part of the DIGIMIC lean+ signature series.