

DIGIMIC DLine

Dual line in, 19", 1HU

Article no.: 05.0060



Description

DLine is a high quality audio input device to feed 2 independent line level audio signals into the DIGIMIC conference system. The audio sources can be switched from the front plate or controlled via software like any other delegate microphone unit.

Any audio source within the conference system can easily be controlled via named buttons on a mimic panel to ensure the best overview of all audio input sources.

Features

Digital Audio

- High quality digital audio:
- Sample Rate: 48 kHz
- Frequency response: 20 - 20,000 Hz

Connectors

- 2x XLR input, transformer balanced
- 2x RJ45 in/out for each unit

Features

- 2 independent line level inputs for external audio feed into a DIGIMIC conference system
- 0 dB, balanced
- Alternatively available with mic level sensitivity
- 2x illuminated front switch button
- Switching of audio signal via any DIGIMIC microphone control software

Housing

- Housing front plate: aluminium
- housing rear: stainless steel
- W x H x D:
482.6 x 44.4 x 45 mm
19 x 1.75 x 1.75 inch
- Weight: approx. 750 g

System requirements

Supported Central Control Units

- D Cen
Article no.: 05.0010
- D Cen mini
Article no.: 05.0410

Other Components

- DDol Interpreter Console
Article no.: 05.0700
- DExt Extension Power Supply
Article no.: 05.0025

Software

brählerOS to manage DIGIMIC hardware.
Easy configuration of all delegate units from a single point.